



OxLIFE INDEPENDENCE





THE PIECE THAT COMPLETES YOUR NEEDS.

The Oxlife Independence by O2 Concepts is a portable oxygen concentrator designed with both patients and providers in mind. Boasting both continuous flow up to 3L/min and pulse settings up to 6 (96 mL), the Oxlife Independence gives patients total freedom with 24/7 oxygen on the go while offering providers a one solution approach to maximize profits in today's turbulent reimbursement climate.

-  Patent-pending ESA technology enables the Oxlife Independence to have the longest battery life in its class

- Only POC in class that can be used on all settings while plugged in car (DC) mode



- Integrated DC power supply -no external brick

- Custom split battery configuration allows for "hot swapping" of battery. No loss of oxygen when switching battery

- Integrated cart kit design offers lighter overall weight

- Integrated cart with 6" wheels offers "best in class" mobility

- Medicare HCPCS codes E1390/E1392



- Convenient access to preventative maintenance door for fast and easy pump filter change

- FAA Approved 

PULSE FLOW SETTINGS



- Pulse flow settings in .5 increments for better patient titration
- Large intuitive LCD screen eliminates patient confusion

SETTING	DOSAGE (ML)
.5	8
1	16
1.5	24
2	32
2.5	40
3	48
3.5	56
4	64
4.5	72
5	80
5.5	88
6	96

PRODUCT SPECIFICATIONS*

DIMENSIONS	Height: 20.2" • Width: 10.9" • Depth: 8"
WEIGHT**	Device: 16.7 lbs • Battery: 1.35 lbs/each
OXYGEN FLOW RATE	Pulse Dose Settings 0.5-6 in 0.5 increments (8mL-96mL) 1-3 LPM in Continuous Mode in 0.5 LPM increments
BATTERY DURATION***	5.75 hours @ 2 pulse at 20 bpm • 2.5 hours @ 2 LPM continuous
SOUND LEVEL @ 2 PULSE	40 dBA
BATTERY RECHARGE TIME****	1.5 hours - 1 battery • 2.5 hours - 2 batteries
OXYGEN CONCENTRATION	95.6% - 87% at Sea Level at all settings
OXYGEN OUTPUT PRESSURE	5 psig +/- 1 psig (34 +/- 7 kPa)
AC POWER	Universal Input: 100-240 VAC • 50-60 Hz • 2.0 Amps Output: 24 Volts • 6.3 Amps
DC POWER	12 - 15 VDC • 10 Amps
OPERATING TEMPERATURE	50°F (10°C) to 104°F (40°C)
ALTITUDE OPERATING RANGE	0 - 13,123 Feet (0 - 4,000 Meters)
TRANSPORTATION/STORAGE TEMPERATURE	-4°F (-20°C) to 140°F (60°C)
TRANSPORTATION/STORAGE HUMIDITY	0 - 95% Non-Condensing
WARRANTY	3 Year Limited • 1 Year on Accessories/Battery



*O2 CONCEPTS RESERVES THE RIGHT TO CHANGE SPECIFICATIONS OF THIS PRODUCT AT ANYTIME WITHOUT NOTICE

**PRODUCTION WEIGHT DOES NOT INCLUDE CART KIT

***BATTERY DURATION SHOWN IS FOR EXTENDED BATTERY SYSTEM

****BATTERY RECHARGE TIME WILL INCREASE IF UNIT IS RUNNING WHILE CHARGING

ORDERING INFORMATION*

PART DESCRIPTION	PART NUMBER
SYSTEMS	
OXLIFE INDEPENDENCE POC STANDARD SYSTEM The Oxlife Independence POC Standard System includes oxygen concentrator, 1 battery, pull handle and wheels, AC and DC power supplies, accessory bag and user manual.	800-0001-1
OXLIFE INDEPENDENCE POC EXTENDED BATTERY SYSTEM The Oxlife Independence POC Extended Battery System includes oxygen concentrator, 2 batteries, pull handle and wheels, AC and DC power supplies, accessory bag and user manual.	800-0001-2
ACCESSORIES	
AC POWER CORD/POWER SUPPLY	800-1000
DC POWER CORD	800-1001
BATTERY - LITHIUM ION RECHARGEABLE	800-1002
ACCESSORY CARRY BAG	800-1003
BATTERY CHARGER - DESK TOP SINGLE BAY	800-1004
BATTERY CHARGER - MULTIPLE (6 BAY)	800-1005
INLET AIR FILTER (PACK OF 6)	800-1006
WHEELS (2)	800-1007
USER MANUAL	800-1008
PROTECTIVE COVER	800-1009
CART KIT (INCLUDES WHEELS AND PULL HANDLE)	800-1010
PULL HANDLE KIT	800-1011

*US FEDERAL LAW RESTRICTS THESE DEVICES TO SALE BY OR ON THE ORDER OF A PHYSICIAN



14001 MCAULEY BLVD, SUITE 170 . OKLAHOMA CITY, OK 73134
T: 877-867-4008 . F: 877-867-1314 . WWW.O2-CONCEPTS.COM



PROUDLY MADE IN THE USA

MKT-0001 Rev: C